This file has been cleaned of potential threats.

To view the reconstructed contents, please SCROLL DOWN to next page.



प्लाज्मा अनुसंधान संस्थान INSTITUTE FOR PLASMA RESEARCH परमाणु ऊर्जा विभाग, भारत सरकार का एक सहायता प्राप्त संस्थान



An Aided Institute of Department of Atomic Energy, Government of India

इन्दिरा पुल के पास, भाट, गांधीनगर – 382 428 भारत दूरभाष: (079) 2396 2020/2021/2028 फैक्स: 91-079-23962277 वेब: <u>www.ipr.res.in</u> NEAR INDIRA BRIDGE, BHAT DIST. GANDHINAGAR - 382 428 (INDIA) Phone: (079) 2396 2000/2026/2332 Fax : 91-079-23962277 Web : <u>www.ipr.res.in</u>

ENQUIRY	
ENQUIRY NO Date	: IPR/EQF/19-20/091 : 16-07-2019
Due on	: 29-08-2019 by 1:00 PM IST

Please send your offer in sealed envelope specifying Enquiry No, Date & Due Date, ALONG WITH your credentials for the following items which we are interested to import directly against Foreign Trade Policy 2015-2020.

Important Note:

Please note that e-mail quotations are not acceptable however you may send your queries (if any) to <u>importpurchase@ipr.res.in</u>

Please ensure your sealed quotation reaches this office not later than above mentioned due date and time.

Kindly go through the following documents properly before quoting which are available on the IPR web portal i.e., <u>http://www.ipr.res.in/documents/tender_terms.html</u> / attached herewith.

- 1) Instructions to the bidders & Terms and conditions (refer Form No: IPR-FP-01.V3)
- 2) Bidding format

GST for Goods and Services (IGST/CGST/SGST TAX BENEFITS): Please refer **clause no:** 14 of Form No: **IPR-FP-01.V3**

QUOTATION SHOULD BE ADDRESSED TO PURCHASE OFFICER ONLY

Sr No	Description	
1	Pulsed Current transformers a sper enclosed speciofications	3.0 Nos.
Note:		
Encl:	As per attached.	Sd/-

Information to Vendors: We are working towards a single platform for our future requirement. Hence, please refer IPR website i.e, http://www.ipr.res.in/documents/tenderseng.html for our future requirement.

Pulse Current Transformer

Specifications :

Output sensitivity	:	0.1 volt/Ampere,			
Output resistance	:	50 Ohms			
Output connector	:	BNC			
Hole diameter	:	2.37 inch (quote typical)			
Maximum peak current	:	5 Kilo Ampere			
Rise time	:	\leq 20 - 35 ns (typical or quote)			
Maximum RMS Current (Continuous) : ≥ 150 Ampere					
High frequency 3 db point :	≥ 13.5	56 M Hz.			
Quantity	:	3 no.s			

The Vendor must submit the technical specifications of quoted model, Data sheet reflecting the typical drawings, any deviations can be stated with specifications enclosed. . We need to use for 13.56 MHz RF power source current monitoring applications of upto 5 kW Power.

Sr No			Vendor Specifications	
1.			-	
2.	Output resistance	50 Ohms		
3.	Output connector	BNC		
4.	Hole diameter	2.37 inch (quote typical)		
5.	Maximum peak current	5 Kilo Ampere,		
6.	Rise time	≤ 20 nsec (typical or quote)		
7.	Maximum RMS Current (Continuous)	≥150 Ampere,		
8.	High frequency 3db point	≥ 13.56 MHz.		
9.	Quantity	3 no.s		
10.	The Vendor must submit the technical specifications of quoted model, Data sheet reflecting the typical drawings, any deviations can be stated with specifications enclosed We need to use for 13.56 MHz RF power source current monitoring applications of upto 5 kW Power.			

Bidder's Official Stamp and Sign:

Date: