his file has been cleaned of potential threats.	
o view the reconstructed contents, please SCROLL DOWN to next page.	



प्लाज्मा अनसधान सस्थान INSTITUTE FOR PLASMA RESEARCH



परमाणु ऊर्जा विभाग, भारत सरकार का एक सहायता प्राप्त

An Aided Institute of Department of Atomic Energy, **Government of India**

इन्दिरा पुल के पास, भाट, गांधीनगर - 382 428 भारत

द्रभाष: (079) 2396 2020/2021/2028 फैक्स: 91-079-23962277

वेब: www.ipr.res.in

NEAR INDIRA BRIDGE, BHAT

DIST. GANDHINAGAR - 382 428 (INDIA) Phone: (079) 2396 2020/2021/2028

Fax: 91-079-23962277 Web: www.ipr.res.in

ENQUIRY

ENQUIRY NO : IPR/EQL/18-19/347

Date : 09-01-2019

: 07-02-2019 by 1:00 PM IST Due on

Please send your offer in sealed envelope specifying Enquiry No, Date & Due Date, ALONG WITH your credentials for the following items:

Important Note:

Please note that e-mail quotations are not acceptable however you may send your queries (if any) to localpurchase@ipr.res.in

Please ensure your sealed quotation reaches this office not later than above mentioned due date and time.

Kindly go through the following documents properly before quoting which are available on the IPR web portal i.e., http://www.ipr.res.in/documents/tender_terms.html / attached herewith.

- 1) Instructions to the bidders & Terms and conditions (refer Form No: IPR-LP-01.V4)
- 2) Bidding format

GST for Goods and Services (IGST/CGST/SGST TAX BENEFITS): Please refer clause no: 8 of Form No: IPR-LP-01.V4

QUOTATION SHOULD BE ADDRESSED TO PURCHASE OFFICER ONLY

Sr No	Description	
1	3 Axis RF field strength meter	1.0 Nos.

Note: TDS as per CGST Act: As per provisions of section No. 51 of

> the CGST Act 2017, TDS @2% (IGST 2% or CGST 1% and SGST 1%) will be deducted while making payment to the suppliers where total value of orders/contracts/work orders exceeds Rs. 2.5 lakhs, in the event of order in Indian Rupees. Necessary TDS Certificate will be issued to the supplier after

TDS deduction.

Encl: As per attachment.

Sd/-

Mr. D. Ramesh Purchase Officer-II

Information to Vendors: We are working towards a single platform for our future requirement. Hence, please refer IPR website i.e,

http://www.ipr.res.in/documents/tenderseng.html for our future requirement.

3 - Axis RF Field Strength Meter

Specifications

Measuring Range

: 38mV to 20 v/m

Frequency Range

: 10MHz - 8GHZ

Sensor

: Triple Axis (X, Y, Z)

Manual Data Memory

: Max & AVG Records

Measurement Units

: mv/m , v/m , $\mu A/m$, mA/m , $\mu W/m2$, mW/m2

, µW/cm2

Display Resolution

 $: 0.1 \text{mv/m}, 0.1 \mu\text{A/m}, 0.001 \mu\text{W/m}2,$

 $0.001 \mu W/cm2$

Manual Data Memory

: Read storage -- 200 data sets

Alarm Function

. Adjustable

Calibration Factor CAL

: Adjustable threshold with ON/ OFF

Sampling Time

: 2.5 times per second

Operating Temp. & RH

: 0 to 50°C (32°F to 122°F). Max. 80% RH.

Power Supply

: 9V battery /Quote

Battery life

: Quote

Weight

: Quote

Size

: Quote.

Accessories

: Instruction Manual and hard carrying case

Warranty

: 1 year

The vendor shall submit the test certificates

Quantity

: 1 no.