his file has been cleaned of potential threats.	
o view the reconstructed contents, please SCROLL DOWN to next page.	



प्लाज्मा अनुसंधान संस्थान INSTITUTE FOR PLASMA RESEARCH परमाण् ऊर्जा विभाग, भारत सरकार का एक सहायता



प्राप्त संस्थान

An Aided Institute of Department of Atomic Energy, **Government of India**

इन्दिरा पुल के पास, भाट, गांधीनगर - 382 428 भारत

द्रभाष: (079) 2396 2020/2021/2028

फैक्स: 91-079-23962277

वेब: www.ipr.res.in

NEAR INDIRA BRIDGE, BHAT

DIST. GANDHINAGAR - 382 428 (INDIA) Phone: (079) 2396 2020/2021/2028

Fax : 91-079-23962277

Web: www.ipr.res.in

ENQUIRY

ENQUIRY NO

: IPR/EQL/19-20/150

Date

: 12-07-2019

Due on

: 25-07-2019 by 1:00 PM IST

Please send your offer in sealed envelope specifying Enquiry No, Date & Due Date, ALONG WITH your credentials for the following items:

Important Note:

Please note that e-mail quotations are not acceptable however you may send your queries (if any) to localpurchase@ipr.res.in

Please ensure your sealed quotation reaches this office not later than above mentioned due date and time.

Kindly go through the following documents properly before quoting which are available on the IPR web portal i.e., http://www.ipr.res.in/documents/tender_terms.html / attached herewith.

- 1) Instructions to the bidders & Terms and conditions (refer Form No: IPR-LP-01.V4)
- 2) Bidding format

GST for Goods and Services (IGST/CGST/SGST TAX BENEFITS): Please refer clause no: 8 of Form No: IPR-LP-01.V4

QUOTATION SHOULD BE ADDRESSED TO PURCHASE OFFICER ONLY

Sr No	Description	Quantity
	SS 304 Finished sheet, size: 8' x 4' x 8 mm thickness (Nos: 2) (ASME SA240/SA240M and/or ASME SA480/SA480M)	400.0 Kgs
	SS 304 Finished sheet, size: 8' x 4' x 10 mm thickness (Nos: 2) (ASME SA240/SA240M and/or ASME SA480/SA480M)	500.0 Kgs

SS 304 Finished sheet, size: 8' x 4' x 14 mm thickness (Nos:4) (ASME SA240/SA240M and/or ASME SA480/SA480M)	1360.0 Kgs
SS 304 Finished sheet, size: 8' x 4' x 18 mm thickness (Nos:4) (ASME SA240/SA240M and/or ASME SA480/SA480M)	1750.0 Kgs

Note: 1. Delivery Time: 10 Days

2.TDS as per CGST Act: As per provisions of section No. 51 of the CGST Act 2017, TDS @2% (IGST 2% or CGST 1%) will be deducted while making

1% and SGST 1%) will be deducted while making payment to the suppliers where total value of

orders/contracts/work orders exceeds Rs. 2.5 lakhs, in the event of order in Indian Rupees. Necessary TDS Certificate will be issued to the supplier after TDS

deduction.

Encl: As Per Attachment

Sd/-

Mr. D. Ramesh Purchase Officer-II

Information to Vendors: We are working towards a single platform for our future requirement. Hence, please refer IPR website i.e, http://www.ipr.res.in/documents/tenderseng.html for our future requirement.

Compliance Form

Sr. No.	IPR Requirement	Vendor Specification
1	SS 304 Finished sheet, size: 8' x 4' x 8 mm thickness(Nos:2) (ASME SA240/SA240M and/or ASME SA480/SA480M)	A Maria Maria (Maria Maria Mar
2	SS 304 Finished sheet, size 8' x 4' x 10 mm thickness(Nos:2) (ASME SA240/SA240M and/or ASME SA480/SA480M)	Adam and a sur but the sure of
3	SS 304 Finished sheet, size: 8' x 4' x 14 mm thickness(Nos:4) (ASME SA240/SA240M and/or ASME SA480/SA430M)	designation belongs of the successor
4	SS 304 Finished sheet, size 8' x 4' x 18 mm thickness(Nos:4) (ASME SA240/SA240M and/or ASME SA480/SA430M)	match with one Asion. Section grade SA 240 goode 300 material will be o

Other Details

Sr. No.	IPR Requirement	Ver dor Specification
	Material Test certificate is required with the	
1	supply of the material for each thickness.	See Section . Living and the Automotive Section .
0	More than 5% weight is not accepted in above	
2	individual items.	
3	Material should not be bend and required good	Charles Addition to the
3	finished.	MA MA TERMINITARY OF A STATE OF THE STATE OF
	Material will be rejected if chemical compostion	
4	and physical properties of supplied material is not	
4	match with the ASME SA240 grade 304 material.	

	SA 240 grade 304 material will be required with	
	following chemical and physical properties:-	
	Carbon 0.08 max.	
	Manganese 2.00 max.	
	Phosphorus 0.045 max.	
	Sulfur 0.030 max.	
5	Silicon 0.75 max.	
5	Chromium 18.00-20.00	
	Nickel 8.00-12.00	
	Nitrogen 0.10 max. Yield strength minimum 205 Mpa	
	Tensile strength minimum 515 Mpa	
	Elongation minimum 40%	
	Elongation minimum 4070	
	Each Sheet is required with Heat mark or Batch	control and that is regulated to the second and the
	number with respect to material test certificate.i.e.	
	The Heat mark or Batch number of each sheet	
6	should be match with the material test certificate	
	which will be provided by the vendor	
	which will be provided by the vender	
	Supplier has to specify the make of material with	PARTIES AND PARTIES CO. T. P. C.
7	the quotation.	