his file has been cleaned of potential threats.	
o view the reconstructed contents, please SCROLL DOWN to next page.	



प्लाज़मा अनुसंधान संस्थान INSTITUTE FOR PLASMA RESEARCH परमाणु ऊर्जा विभाग, भारत सरकार का एक सहायता



प्राप्त संस्थान

An Aided Institute of Department of Atomic Energy, Government of India

इन्दिरा प्ल के पास, भाट, गांधीनगर - 382 428 भारत

दूरभाष: (079) 2396 2020/2021/2028

फैक्स: 91-079-23962277

वेब: www.ipr.res.in

NEAR INDIRA BRIDGE, BHAT

DIST. GANDHINAGAR - 382 428 (INDIA) Phone: (079) 2396 2020/2021/2028

Fax : 91-079-23962277

Web : www.ipr.res.in

ENQUIRY

ENQUIRY NO

: IPR/EQL/19-20/151

Date

: 12-07-2019

Due on

: 25-07-2019 by 1:00 PM IST

Please send your offer in sealed envelope specifying Enquiry No, Date & Due Date, ALONG WITH your credentials for the following items:

Important Note:

Please note that e-mail quotations are not acceptable however you may send your queries (if any) to localpurchase@ipr.res.in

Please ensure your sealed quotation reaches this office not later than above mentioned due date and time.

Kindly go through the following documents properly before quoting which are available on the IPR web portal i.e., http://www.ipr.res.in/documents/tender_terms.html / attached herewith.

- 1) Instructions to the bidders & Terms and conditions (refer Form No: **IPR-LP-01.V4**)
- 2) Bidding format

GST for Goods and Services (IGST/CGST/SGST TAX BENEFITS): Please refer clause no: 8 of Form No: IPR-LP-01.V4

QUOTATION SHOULD BE ADDRESSED TO PURCHASE OFFICER ONLY

Sr No	Description	Quantity
	SS 304 Finished sheet, size: 8' x 4' x 20 mm thickness (Nos: 2) (ASME SA240/SA240M and/or ASME SA480/SA480M)	980.0 Kgs
	SS 304 Finished sheet, size: 8' x 4' x 22 mm thickness (Nos: 2) (ASME SA240/SA240M and/or ASME SA480/SA480M)	1080.0 Kgs

3 SS 304 Finished sheet,size:8' x 4' x 25 mm thickness(Nos:2) (ASME SA240/SA240M and/or ASME SA480/SA480M) 1240.0 Kgs

Note: Delivery Time: 10 Days

TDS as per CGST Act: As per provisions of section No. 51 of the CGST Act 2017, TDS @2% (IGST 2% or CGST 1% and SGST 1%) will be deducted while making payment to the suppliers where total value of orders/contracts/work orders exceeds Rs. 2.5 lakhs, in the event of order in Indian Rupees. Necessary TDS Certificate will be issued

to the supplier after TDS deduction.

Encl: As Per Attachment

Sd/-

Mr. D. Ramesh Purchase Officer-II

Information to Vendors: We are working towards a single platform for our future requirement. Hence, please refer IPR website i.e, http://www.ipr.res.in/documents/tenderseng.html for our future requirement.

Compliance Form

Sr. No.	IPR Requirement	Vendor Specification
1	SS 304 Finished sheet, size: 8' x 4' x 20 mm thickness (Nos: 2) (AS ME SA240/SA240M and/or ASME SA480/S 4480M)	Augustus
2	SS 304 Finished sheet,size:8' x 4' x 22 mm thickness(Nos:2) (ASME \$A240/\$A240M and/or ASME \$A480/\$ 4180M)	Control of the state of the sta
3	SS 304 Finished sheet,size:8' x 4' x 25 mm thickness(Nos:2) (AS ME SA240/SA240M and/or ASME SA480/S 4480M)	er for brod od top bisese is top

named commune Access access of the majored with following characters and physical or performances a state of the commune of th

mumber with respect to postative sees continued in the rices mark or best pumber of seeds should be resuch with the material test continued which will be provided by the tendor

Supplier has to specify the make of annerial war-

Other Details

Sr. No.	IPR Requirement	Veudor Specification
1	Material Test certificate is required with the supply of the material for each thickness.	
2	More than 5% weight is not accepted in above individual items.	
3	Material should not be bend and required good finished.	
4	Material will be rejected if chemical compostion and physical properties of supplied material is not match with the ASME SA240 grade 304 material.	
5	SA 240 grade 304 material will be required with following chemical and physical properties:- Carbon 0.08 max. Manganese 2.00 max. Phosphorus 0.045 max. Sulfur 0.030 max. Silicon 0.75 max. Chromium 18.00-20.00 Nickel 8.00-12.00 Nitrogen 0.10 max. Yield strength minimum 205 Mpa Tensile strength minimum 515 Mpa Elongation minimum 40%	
6	Each Sheet is required with Heat mark or Batch number with respect to material test certificate.i.e. The Heat mark or Batch number of each sheet should be match with the material test certificate which will be provided by the vendor	
7	Supplier has to specify the make of material with the quotation.	